Description

Method and device for regulating an internal combustion engine

5   The invention relates to a method for regulating an internal
     combustion engine according to one or more physical models,
     wherein measurement values and adjustment values are provided
     as system parameters underlying the physical model. The
     invention also relates to a device for regulating an internal
10   combustion engine according to one or more physical models.

     Engine controls for internal combustion engines normally use
     physical models which have parameters by means of which the
     ideal state of the internal combustion engine can be
15   described. In reality, the underlying parameters of the
     physical model generally deviate from the real parameters of
     the engine. In order to match the physical models to the
     actual conditions in the internal combustion engine,
     adaptations of the parameters are carried out which are based
20   on a comparison between measured parameters and theoretically
     expected values. The parameters are adapted by applying one or
     more adaptation values to said parameters.

     It is desirable for the adaptations to be executed such that
25   adaptation values are applied to those parameters of the
     physical models which are actually the cause of the deviation
     between the physical models and the real conditions in the
     internal combustion engine. If those parameters which are
     actually the cause of the deviation between model and reality
30   are adjusted with the aid of adaptation values, the physical
     models deliver precise results even when there are rapid
     changes in the working point of the internal combustion engine
     without a repeat adaptation being required. If other

parameters are adapted which are not the cause of the
deviation between model and the real conditions, then a repeat
adaptation is generally required when there is a change in the
working point. The assignment of deviations to the correct
5   system parameters (parameters) can, however, be difficult
since the number of sensors for measuring the parameters is
frequently limited.

Such a problem is present in internal combustion engines which
10   have an intake manifold pressure sensor in an intake pipe but
do not have an air mass sensor, particularly in internal
combustion engines with variable valve control. The intake
manifold pressure in such systems depends above all on the
flow cross-section at a throttle valve and on the absorption
15   capacity of the engine. The absorption capacity of the engine
is essentially determined by the settings of the intake and
outlet valves and/or by the rotational speed of the internal
combustion engine. If the intake manifold pressure sensor
identifies an intake manifold pressure which is higher than
20   the theoretically expected value, then this may be caused by a
greater flow cross-section at the throttle valve then
specified by the corresponding parameter or by a lower
absorption capacity than specified by the corresponding
parameter. If in this state the flow cross-section of the
25   throttle valve is adapted upwardly, then the calculated air
mass becomes too great and the injection quantity is
mistakenly raised. This results in too rich an air/fuel ratio
in the combustion chamber of the internal combustion engine.
The air/fuel ratio that is too rich can be detected by means
30   of the lambda probe. The measured air/fuel ratio leads to an
adaptation of the quantity of fuel injected, which is reduced
as result, i.e. the corresponding adaptation value for the
fuel quantity is decreased. The desired air/fuel ratio can in

this way be maintained. Although the model for a specified
working point of the internal combustion engine can in this
way be brought into harmony with the measurement values,
nonetheless incorrect parameters are adapted which determine

5   at another working point defective model parameters so that an
adaptation has to be carried out afresh. Under changing
operating conditions, this would result in the underlying
physical model having to be adapted constantly to the changed
operating state. As a result, an adaptation of the physical

10   model can be implemented only when the operating state is
static.

Such a physical model for determining the air mass flow, which
is determined with the aid of the measured intake manifold

15   pressure, is known from publication WO 97/35106. Furthermore,
an adaptation is provided for permanently adjusting the model
parameters in a stationary and in a nonstationary operation in
order to adapt the accuracy of the selected physical model.

20   The object of the present invention is to provide a method for
controlling an internal combustion engine according to one or
more physical models, wherein the parameters of the physical
model can be adapted in an improved way. There is also
provided a device for controlling an internal combustion

25   engine which has a control based on one or more physical
models, wherein the parameters of the physical model(s) are
adapted in an improved way.

This object is achieved in the method according to Claim 1.

30

Further advantageous embodiments of the invention are
specified in the dependent claims.

According to a first aspect of the present invention, a method
is provided for controlling an internal combustion engine
according to one or more physical models. Measurement values
and adjustment values are provided as system parameters which
5   underlie the physical model. One or more adaptation values,
respectively, can be applied to the system parameters in order
to adapt the physical model to real conditions of the internal
combustion engine. Estimation parameters are determined by
means of the system parameters, measurement parameters being
10   determined in a measurement of the physical parameters
underlying the estimation parameters. The measurement
parameters are evaluated in relation to the estimation
parameters and determined in accordance with an adaptation
method with the aid of the measurement parameter adaptation
15   values for at least a part of the system parameters. Depending
on the adaptation values, a first operating mode or a second
operating mode is adopted. The adaptation method is preferably
implemented in the first operating mode and a further
adaptation method implemented in the second operating mode.
20

In a preferred embodiment, a first estimation parameter and a
second estimation parameter are determined by means of a first
system parameter and/or a second system parameter and/or a
third system parameter. In a measurement of a physical
25   parameter underlying the first estimation parameter, e.g. in
an exhaust pipe, a first measurement parameter is determined
and in a measurement of a physical parameter underlying the
second estimation parameter, e.g. in an intake pipe, a second
measurement parameter is determined. The first measurement
30   parameter is evaluated in relation to the first estimation
parameter and the second measurement parameter is evaluated in
relation to the second estimation parameter, a first
adaptation value of the first system parameter being

determined with the aid of the first measurement parameter. In
a first operating mode, a second adaptation value for the
second system parameter is determined with the aid of the
second measurement parameter and a third adaptation value for
5   the third system parameter is left unchanged. A change in the
second adaptation value causes, due to the regulation, a
change in the first system parameter. A second operating mode
is adopted if the first adaptation value determined deviates
from a neutral value by a first absolute on relative deviation
10   value and the second adaptation mode determined in the first
operating mode deviates by a second absolute or relative
deviation value from a neutral value. In the second operating
mode, the second adaptation value for the second system
parameter is reset and the third adaptation value for the
15   third system parameter determined with the aid of the second
measurement parameter, the second adaptation value for the
second system parameter being left unchanged after the
resetting.

20   The inventive method has the advantage that when the system
parameters underlying a physical model are adapted using
measurement values, those system parameters are adapted which
are probably the cause of the deviation of the actual
conditions and the theoretical model. Since as a rule only a
25   limited number of sensors are provided which can be used for
adapting system parameters of the physical model, it
frequently cannot be determined unambiguously which of the
system parameters has to be adapted due to a deviation of a
measured value from a theoretically expected value. This is
30   the case when the deviation from the theoretically expected
value can be caused by two or more deviations of system
parameters.

If, when the physical model is adapted, two measurement parameters are determined, the adaptation of the second system parameter due to the regulation resulting in the first system parameter having to be readapted, then it can be assumed with

5 a certain degree of probability that instead of the second system parameter the third system parameter has to be adapted if the adaptation value determined deviates from the neutral value by the first deviation value and second adaptation value deviates from the neutral value by the second deviation value.

10 The neutral value is determined by the value at which no deviation is present, i.e. no adaptation has had to be or will have to be undertaken.

Thus, if it is ascertained that a second adaptation value,

15 which in the course of the adaptation was changed by a specified deviation value, has to be applied to the second system parameter, and simultaneously a first adaptation value has to be applied to the first system parameter, then it may be obvious for the third system parameter to be adapted

20 instead of the second system parameter and for the previous adaptation of the second system parameter to be returned to the initial value.

The advantage of the inventive method is that it can be

25 ascertained from adaptation values already determined whether the adaptation of one of the system parameters corresponds to a deviation of a physical parameter underlying the system parameter or whether a deviation of another system parameter is present. If this is ascertained, according to the invention

30 the adaptation of the second system parameter is terminated and an adaptation of the third system parameter carried out instead.

In principle, the system parameters of the physical model can be adapted in a random manner in order to provide suitable adapted system parameters for a specified working point. The adaptation of those system parameters which are responsible

5 for the deviation between the estimation parameter and the measured value is, however, advantageous since, when there is a change in the engine working point no substantial change in the adaptation values is necessary if the correct system parameters have been adapted. If the wrong system parameters

10 have been adapted, then a repeat adaptation is necessary at each new engine working point.

It can preferably be provided that the resetting of the second adaptation value is carried out gradually so that no abrupt

15 change in the model parameters leads to an abrupt change in the third adaptation value. This could lead to a fluctuation of the physical model parameters since a change in a system parameter frequently leads to a change in a further system parameter only after a defined cycle time, so the adaptations

20 of the system parameters would occur at staggered times relative to one another.

Alternatively, when the second adaptation value is reset, the second adaptation value can be switched to a corresponding

25 modification of the first adaptation value and/or a corresponding third adaptation value. In this way, it is also possible to establish a "gentle" transition between the first and second operating modes.

30 Advantageously, the second operating mode is adopted if the first adaptation value determined is increased relative to the neutral value by the amount of the first deviation value and the second adaptation value determined in the first operating

mode is reduced relative to the neutral value by the amount of
the second deviation value or if the first adaptation value
determined is reduced relative to the neutral value by the
amount of the first deviation value and the second adaptation

5   value determined in the first operation mode is increased
relative to the neutral value by the amount of the second
deviation value.

It can be provided that the first operating mode is adopted
10 each time the internal combustion engine is started.

It can also be provided that after a specified period of time
after the second operating mode has been adopted a switchover
is made from the second operating mode to the first operating
15 mode without the third adaptation value being reset. In this
way, it is possible that after the adaptation of the third
adaptation value in the first operating mode the second
adaptation value can also be modified again and that an
adaptation of the third and of the second adaptation value is
20 possible.

A parameter which influences the opening time of a fuel
injection valve is preferably provided as a first system
parameter and/or a flow cross-section of the airflow let into
25 the intake pipe as a second system parameter and/or an
absorption characteristic curve of the internal combustion
engine or a valve setting of an intake and/or outlet valve as
a third system parameter.

30 It can also be provided that the air/fuel ratio in an exhaust
pipe of the internal combustion engine is determined as a
first measurement value and/or the intake manifold pressure in
an intake manifold of the internal combustion engine as a

second measurement value.

A preferred embodiment of the invention is explained in detail
below with reference to the attached drawings, in which:

5

Figure 1   shows a schematic model of an internal combustion
              engine;

Figure 2   shows a diagram of the absorption behavior of the
10   internal combustion engine; and

Figure 3   shows two flow diagrams for illustrating the
              inventive method.

15   Figure 1 shows schematically an internal combustion engine
     comprising a cylinder 1. The cylinder 1 has a piston 2 and a
     combustion chamber 3. A fuel/air mixture is supplied in an
     intake manifold 4 and can be let into the combustion chamber 3
     via an intake valve 5.

20

     There is also provided an outlet valve 6 which is disposed on
     the combustion chamber 3 in order to discharge exhaust gas
     into an exhaust pipe 7. The setting (relative opening and
     closing times) of the intake valve 5 and of the outlet valve 6
25   are controlled by a regulating unit (not shown) and are set
     with regard to the absorption behavior of the system as a
     whole.

     Also disposed on the intake manifold 4 is an injection valve 9
30   in order to inject fuel. The quantity of fuel injected is
     determined by the opening time of the injection valve 9. The
     opening time of the injection valve 9 is controlled by the
     regulating unit (not shown). The intake manifold 4 is also

connected to an air feed 10 in order to feed air with a
defined air mass flow to the intake manifold 4. A throttle
valve is disposed in the air feed 10, which throttle valve can
swivellably control the air mass flow into the intake manifold
5   4. The throttle valve has a flow cross-section that depends on
the control. The throttle valve 11 can be controlled via the
regulating unit (not shown).

The internal combustion engine according to Figure 1 is based
10   on a physical model, according to which the mass flows into
the intake manifold 4 and out of the intake manifold 4
determine the pressure in the intake manifold 4. The pressure
in the intake manifold 4 is essential to control of the
internal combustion engine since the mass flow into the
15   cylinder 1 is determined by means of the pressure and the
absorption characteristic curve of the cylinder 1. Since the
settings of the intake and outlet valves, i.e. their phase
position, influence the absorption behavior of the cylinder 1,
precise knowledge of the absorption behavior is required.
20   According to a physical model on which the internal combustion
engine is based, the pressure in the intake manifold is
determined by:

$$\dot{P}_{im} = \frac{R_g \cdot T_{im}}{V_{im}} (\dot{m}_{thr} - \dot{m}_{cyl})$$

25

where T corresponds to the temperature in the intake manifold,
V_{im} to the volume of the intake manifold, $\dot{m}_{thr}$ to the air mass
flow into the intake manifold, $\dot{m}_{cyl}$ essentially to the intake
quantity of the air/fuel mixture fed to the cylinder 1 and R_g
30   to the gas constant of the air/fuel mixture. The equation
shown represents a physical model by means of which the
pressure in the intake manifold 4 can be determined.

In order to be able to operate the internal combustion engine
1, knowledge of the air mass flow into the intake manifold is
required. Due to component tolerances or other influences on
5   the internal combustion engine, deviations from the
theoretically expected value and the real values of parameters
in the internal combustion engine can arise. For example, the
air mass flow $\dot{m}_{thr}$ into the intake manifold 4 can have a
different value than expected based on the flow cross-section
10   of the throttle valve 11. Such a deviation can arise due to
faults or other tolerances.

It is also possible for the fuel quantity injected by the
injection valve 9 not to match the quantity which would be
15   expected on the basis of the control signal specified for the
injection valve 9. Thus, the quantity of fuel injected is
determined by the opening time of the injection valve 9;
however, due to component tolerances deviations can occur in
the cross-section of the opening of the injection valve 9.
20   Furthermore, deviations can also occur due to component
fluctuations between the calculated exhaust gas flow into the
intake manifold 4 and the real exhaust gas flow into the
intake manifold 4.

25   Using a lambda probe 13, it can be determined whether the
combustion in the cylinder 1 has taken place with too rich an
air/fuel mixture or too lean an air/fuel mixture. By means of
a lambda regulation implemented in the regulating unit, the
value for the air/fuel ratio is fed to a regulation by means
30   of which the opening time of the injection valve 9 and
consequently the quantity of fuel to be injected are
controlled.

In order to establish whether there are deviations between the
theoretically expected values and the real values, a pressure
sensor 14 is disposed in the intake manifold 4 in order to
record the pressure in the intake manifold. The value of the
5 pressure in the intake manifold 4 is made available to the
regulating unit. If the measured pressure deviates from the
pressure theoretically expected in the intake manifold 4, then
there must be a deviation in one of the aforementioned system
parameters.

10

In order to adapt the underlying physical model to reality,
adaptation values are provided for each of the system
parameters. The adaptation values are modifiable and adapt one
or more of the system parameters such that the physical model
15 for the working point adopted in the internal combustion
engine is suitable for describing the overall system so that
control of the throttle valve, the injection valve 9 and the
intake and outlet valves 5, 6 can be implemented optimally for
the internal combustion engine.

20

If the measured pressure in the intake manifold 4 deviates
from the theoretically expected value, then this may point
firstly to an incorrectly determined air mass flow into the
intake manifold 4 and secondly to a deviating absorption
25 behavior of the cylinder 1 relative to an expected absorption
behavior. Where a measured pressure is greater than the
theoretically expected value, this means that the air mass
flow of the air sucked into the intake manifold 4 is greater
than expected on the basis of the flow cross-section of the
30 throttle valve 11. The increased pressure in the intake
manifold 4 can, however, also arise as a result of a deviating
absorption behavior, whereby less of the air/fuel mixture is
let into the combustion chamber 3 than specified on the basis

of the absorption characteristic curve. Since at the same time an adaptation based on the measured pressure can usefully be made either to the flow cross-section of the throttle valve or to the absorption behavior, it may be that an adaptation is

5   made to a system parameter which is not responsible for the deviation in the intake manifold pressure.

If the system parameter of the flow cross-section is adapted, even though the increased pressure in the intake manifold 4 is

10   caused by a deviating absorption behavior of the cylinder 1, then the calculated air mass will be too great and the injection quantity increased mistakenly. The increased injection quantity leads to too rich an air/fuel ratio, which can be determined with the aid of the lambda probe. With the

15   lambda probe, a further adaptation relating to the injection quantity is then carried out, the quantity of fuel being reduced in order to obtain the desired air/fuel ratio. Although in this way the model for a working point of the internal combustion engine can be brought into harmony with

20   the measurement values, the incorrect system parameters are adapted which at a different working point will probably not be appropriate. At a different working point, an adaptation has then to be carried out again, which necessitates a certain period of time during which the internal combustion engine

25   will not be functioning optimally.

If the cause of an increased intake manifold pressure lies in the fact that the absorption behavior of the cylinder 1 is lower than the theoretically expected value, i.e. for a

30   defined valve opening time and valve position a smaller quantity of the air/fuel mixture is let into the combustion chamber 3, then it would be useful to adapt the absorption behavior of the cylinder 1 with the aid of one or more

adaptation values. If, instead, the adaptation value of the flow cross-section is increased, then a further adaptation of the injection quantity based on the measured lambda value causes a change in the adaptation value for the injection

5   quantity. Since applying an adaptation value to the flow cross-section and applying an adaptation value to the injection quantity do not describe the real cause of the deviation in the intake manifold pressure, it is probable that a repeat adaptation of all system parameters will have to be

10   carried out when the working point of the internal combustion engine changes.

Figure 2 shows the characteristic curve of the absorption behavior of the cylinder 1. The absorption characteristic

15   curve is a straight line with an offset value η_{OFS} and a gradient η_{SLOP}. The absorption characteristic curve describes a dependency between the flow of the air/fuel mixture in the cylinder and the pressure in the intake manifold. The offset value η_{OFS} and the gradient η_{SLOP} are parameters which are

20   produced from the respective valve settings of the intake and outlet valves, the rotational speed of the engine and possibly other parameters. When the absorption behavior is adapted, adaptation values can be applied both to the parameters η_{OFS} and/or η_{SLOP} and to the parameters for the valve settings.

25

Figure 3 shows two flow diagrams illustrating the inventive method for adapting the system parameters of flow cross-section, absorption behavior and injection quantity. The adaptation is carried out with the aid of the measured intake

30   manifold pressure and the lambda value of the exhaust gas flowing out of the combustion chamber 3. The adaptation method is implemented as soon as the internal combustion engine is started. Essentially, two adaptations, namely the adaptation

of the injection quantity and the adaptation of the flow
cross-section and/or of the absorption behavior, proceed in
parallel. The adaptations can also be carried out in
succession one after the other.

5

Figure 3 shows two flow diagrams. The first flow diagram shows
the regularly running adaptation of the injection quantity in
accordance with the lambda value determined in the exhaust
pipe 7. After the internal combustion engine has been started
10 in a step S1, a ratio of the air/fuel mixture is calculated
initially for example from the rotational speed of the
internal combustion engine and from the air mass flow which is
to be let into the combustion chamber 3 in order to achieve
the desired operating state of the internal combustion engine
15 (step S2). Ideally, the air/fuel ratio is essentially balanced
so that the air/fuel mixture is neither too rich nor to lean.
If the lambda probe 13 determines in a step S3 that the
mixture is richer than previously calculated, then an
adaptation value for the injection quantity is reduced (step
20 S5) so that the quantity of fuel to be injected is reduced.
This can take place gradually, i.e. in accordance with a fixed
increment or by means of the parameter measured by the lambda
probe 13.

25 If it is not ascertained until a step S4 that the air/fuel
mixture is leaner than calculated, then the injected fuel
quantity has to be increased by increasing the relevant
adaptation value (step S6). The adaptation method for adapting
the injection quantity is implemented periodically so that the
30 adaptation value for the injection quantity is after several
periods set to a value at which the measured air/fuel ratio
matches the calculated air/fuel ratio.

The second flow diagram in Figure 3 shows the adaptation of the flow cross-section or of the absorption behavior of the internal combustion engine according to the invention. The sequence of the second flow diagram runs essentially in
5   parallel with the sequence of the first flow diagram.

After the engine has been started, the system parameters for regulating the internal combustion engine are measured or computationally determined in a step S11 and the theoretically
10   expected intake manifold pressure in the intake manifold 4 determined from the system parameters. Then, in a step S12 the pressure in the intake manifold is measured with the aid of the pressure sensor 14 and compared with the calculated intake manifold pressure. If it is established that the intake
15   manifold pressure is greater than calculated, then it is initially assumed that this is caused by a greater flow cross-section at the throttle valve 11. In this case, the flow cross-section is adjusted upwardly (step S13) so that the calculated air mass flow increases. If the reason for the
20   intake manifold pressure being too high is that the absorption behavior is lower then the expected value and consequently less air/fuel mixture enters the combustion chamber than calculated, the air mass flow is calculated to be too high by the corresponding adaptation value. As a result of too great
25   an air mass flow being calculated, based on the regulation which is designed to preserve a defined air/fuel ratio, the injection quantity of fuel has to be increased in a step S14. The raising of the injection quantity then leads to too rich an air/fuel mixture since the calculated air mass is greater
30   than the air mass really present in the intake manifold 4.

The lambda adaptation according to the first flow diagram in Figure 3 then reduces the injection quantity in order to

obtain the desired air/fuel ratio.

If the intake manifold pressure is lower than calculated (step S15), then the adaptation value for the flow cross-section is reduced so that the calculated air mass is reduced and in accordance with the regulation of the internal combustion engine the injection quantity reduced. This leads to the air/fuel ratio being rendered leaner, whereby the injection quantity is increased if the air/fuel ratio is too lean.

After the adaptation for the flow cross-section has proceeded, a check is carried out to ascertain whether, on the basis of the adaptation values for the injection quantity and the flow cross-section, it can be concluded that a substantial deviation of the real absorption behavior from the ideally expected absorption behavior applies. This is with some probability the case if the adaptation value for the flow cross-section is increased and the adaptation value for the injection quantity is reduced, or vice versa. For a deviation of the adaptation value from a neutral value, defined threshold values are preferably assumed for the percentage deviation or absolute deviation. In this way, a switch can be made, for example, from adaptation of the flow cross-section to adaptation of the absorption behavior of the internal combustion engine if the adaptation value for the flow cross-section is increased by at least a first percentage proportion, e.g. by at least 10%, relative to the neutral value and the adaptation value for the injection quantity is reduced by at least a second percentage proportion, for example also by at least 10%. This also applies if the adaptation value for the flow cross-section is reduced by the first percentage proportion relative to the neutral value and the adaptation value for the injection quantity is increased

by the second percentage proportion relative to the
corresponding neutral value (step S18). If this is not the
case, the process jumps back to step S11 and the adaptation of
the flow cross-section is carried out afresh. If, however,
these deviations are identified, in a following step S19 the
adaptation value for the flow cross-section is reset and the
adaptation for the absorption behavior of the engine begins.
If the measured intake manifold pressure is higher than
expected (step S20), then by applying the appropriate values
η_{SLOP} and η_{OFS}, the absorption behavior is adapted appropriately
(step S21). Alternatively, the adaptation values can also be
applied to the corresponding parameters for the valve
settings. The adaptation values are chosen such that the
calculated absorption behavior is reduced. If the measured
intake manifold pressure is lower than expected (step S22),
then the adaptation value or adaptation values for the
absorption behavior of the internal combustion engine are
correspondingly increased (step S23). Essentially, adaptation
of the injection quantity, in which a modified adaptation
value that is applied to the injection quantity is determined,
is simultaneously continued.

According to one embodiment, it is possible for the resetting
of the adaptation value for the flow cross-section to be
carried out gradually and to be reset by a defined value in
the direction of the neutral value, for example, each time the
adaptation method for the absorption behavior of the internal
combustion engine is run through. Alternatively, it is also
possible to reset the adaptation value for the flow cross-
section to the neutral value at a stroke and simultaneously in
accordance with a predefined calculation formula
computationally to adjust the adaptation value for the
absorption behavior of the internal combustion engine. In both

cases, an abrupt modification of the system parameters can be avoided so that no large target/actual deviation can occur and an oscillation of the regulation can be avoided. In general, no further deviation from the adaptation of the absorption

5 characteristic curve occurs so that no further adaptation of the flow cross-section is possible. Conditions can, however, be defined (step S24) which make it possible for an adaptation of the flow cross-section to be carried out afresh. Such a condition can, for example, be the lapse of a certain period

10 of time so that it is possible after adapting the absorption characteristic curve to carry out a repeat adaptation of the flow cross-section. This is useful since it can occur that both absorption characteristic curve and flow cross-section reveal deviations and thus have to be corrected.

15

The adaptation of the absorption behavior of the internal combustion engine can be effected by adjusting valve control parameters, for example by additional adjustment of the valve overlap or of the intake or outlet valve position.

20

The method described stands solely as an example of a possible way of optimizing the adaptation of system parameters in an overall system which is most likely the cause of the deviation between calculated values and the measured values.

25

The invention consists generally in the fact that, in regulating an internal combustion engine, several deviations between measurement parameters and expected values or several adaptation values with regard to their magnitude and sign are

30 evaluated and the corresponding system parameters for the adaptation selected such that those most likely to be responsible for the deviation between model and reality are adapted. Here, the criterion can generally be applied that the

weighted sum of all adjustments which are necessary for matching modeled parameters and measurement values is minimal. In this process, several different working points of the internal combustion engine are also preferably examined. The criterion can also be applied that the adaptation values for matching modeled parameters and measurement values vary as little as possible across the working points examined.

Generally speaking, a system parameter is selected for adjustment if several deviations between measurement parameters and expected values or several adaptation values point to a deviation of this system parameter in the same direction. It is not absolutely necessary to adapt the system parameters which are most likely to be causing the model deviation by means of an adaptation method; suitable adjustment values can also be calculated directly and applied to the appropriate system parameter. Care must be taken to ensure that the adaptation values of other system parameters are correspondingly reduced, where applicable, in order to avoid an oscillation of the regulating system.